

PB	E	130	230	090	E	1	A1	09	0	0	0
1	2	3	4	5	6	7	8	9	10		
PRODUCT TYPE	DRIVE TYPE	ENGINE TYPE	VOLTAGE	EFFICIENCY GROUP	VALVE TYPE	MODE OF OPERATION OF THE POWERED TOOL	OPERATION OF THE VALVE	TANK CAPACITY	OPTIONS		

1. Product type

PA - compact mini
 PB - compact
 PC - standard
 PD - standard plus

2. Drive type

M- Manual
 E - Electric
 B - Battery
 P - Pneumatic
 G- Diesel

3. Engine type

0,25 - 0,25 kW
 0,37 - 0,37 kW
 0,55 - 0,55 kW
 0,75 - 0,75 kW
 130 - 1,30 kW
 150 - 1,50 kW
 220 - 2,20 kW

4. Voltage

115V - 115
 230V - 230
 380V - 380

5. Efficiency group

0,15 l/min at 700 bar
 0,20 l/min at 700 bar
 0,30 l/min at 700 bar
 0,50 l/min at 700 bar
 0,70 l/min at 700 bar
 0,90 l/min at 700 bar
 1,10 l/min at 700 bar
 1,30 l/min at 700 bar
 1,50 l/min at 700 bar

6. Valve type

R - Manual
 E - Electric
 N - Foot

7. Mode of operation of the powered tool

1 - one-way operation
 2 - two-way operation

8. Operation of the valve

A0 - three-way, two-position
 A1 - three-way, two-position
 B0 - four-way, three-position
 B1 - four-way, three-position

9. Tank capacity

02 - 2 l
 04 - 4 l
 09 - 9 l
 20 - 20 l

10. Options

F - Additional oil filter
 H - Hydraulic hoses
 C - Cooler
 P - Pressure switch
 Q - Quick couplings
 S - Infinitely variable adjustment valve
 M - PLC controller